

SafeNet eToken 5110+ CC authenticator



© 2023 Dot Origin Ltd.

The SafeNet eToken 5110+ is a portable two-factor USB authenticator token that supports secure network logon to Windows, Mac or Linux platforms. It can support authentication and digital signing, as well as secure remote access to VPNs, portals and cloud services. The token requires no special reader or training to use. The token can be developed, by the addition of Java applets, to support other security applications.

This SafeNet eToken 5110+ is CC (EAL5+) qualified. The latest product update has enhanced cryptographic support (including RSA up to 4096 bits and elliptic curve algorithms up to 521 bits).

Fully compliant with the latest Microsoft minidriver specifications for use on Windows, without the need for additional software.

Thales SafeNet part number 909-000167. Gemalto is now part of Thales.

**\*\*\*Call +44 (0)1483 685250 for our best price reseller deals on bulk orders or email [sales@dotdistribution.com](mailto:sales@dotdistribution.com)\*\*\***

**SafeNet eToken 5110+ CC (940B) portable two-factor authenticator token.  
Gemalto (SafeNet) part 909-000167.**

To buy, visit:

<https://www.smartcardfocus.com/shop/ilp/id~990/p/index.shtml>

This Product Briefing has been produced by [Dot Origin Ltd](#), the smart card experts behind [SmartcardFocus.com](#). If you have a query email [sales@smartcardfocus.com](mailto:sales@smartcardfocus.com) or call us on +44 (0)1428 685250.

## **Technical Specifications**

### **Product:**

Credential type(s): USB security token authenticator

Form factor: Portable

Connector: USB Type A, supports USB 1.1 and 2.0

OS support: Windows; Linux; Mac

### **Interface:**

Contact interface standard: ISO 7816

Memory size: 78kB

Memory data retention: At least 10 years

Memory cell rewrites: Min 500 000

Smartcard platform: IDPrime 940B

API and standards support: Base CSP minidriver (SafeNet minidriver); Global platform 2.2.1; Java Card 3.04

Security algorithms: Symmetric - AES secure messaging and 3DES for Microsoft challenge/response only; Hash - SHA-1, SHA-256, SHA-384, SHA-512; RSA up to 4096 bits; RSA OEP and RSA PSS; On-card asymmetric key pair generation (RSA up to 4096 bits and elliptic curves up to 521 bits). P-256, P-384 and P-521 bits ECDSA, ECDH only available via a custom configuration

### **Host Interface:**

USB connector: Type A, supports USB 1.1 and 2.0

Host data transmission speed: 12 Mbps (USB 2.0 full speed and high speed)

### **Certifications:**

Type approvals: CE, FCC, UKCA, RoHS, REACH, WEEE, IEC 62368

Security certifications: CC EAL5+ / PP QSCD, eIDAS qualified for both eSignature and eSeal

Country of origin: China

**Physical:**

Dimensions: 16.4 x 8.5 x 40.2mm (0.65 x 0.33 x 1.6in)

Weight (±5%): 20g

Case: Molded plastic, tamper evident

Water resistance: IP X7 - IEC 60529

**Environment:**

Operating temperature: 0 to 70degC (32 to 158degF)

Storage temperature: -40 to 85degC (-40 to 185degF)

Operating humidity: 0-100% RH (non-condensing)

**Manufacturer's part number:** 909-000167

**Manufacturer:** ACS